



BIOCLEAN CONTROL

The BIOCLEAN Series are a range of peristaltic dosing pumps with digital Timer

General Features

- Flow rate: up to 2 l/h
- Pressure: max 1 bar
- Standard power supply: 230 Vac 50/60 Hz
- Optional power supply: 12Vdc, 120V
- Large LCD display
- Quartzed timer switch with batteries alimentation
- Daily/Weekly programming possibilities
- 8 cycles with 1 minute minimum activation time.
- Repeatable programs
- 24 hours display
- 1 channel
- Programming switch
- Wall mounting

Bioclean CONTROL	Version
CXB 00 551 01	0101
CXB 00 550 01	0201



BIOCLEAN CONTROL/B

The BIOCLEAN Series are a range of peristaltic dosing pumps with digital Timer

General Features

- Flow rate: up to 3 l/h
- Pressure: max 3 bar
- Standard power supply: 230 Vac 50/60 Hz
- Optional power supply: 12Vdc, 120V
- Large LCD display
- Quartzed timer switch with batteries alimentation
- Daily/Weekly programming possibilities
- 8 cycles with 1 minute minimum activation time.
- Repeatable programs
- 24 hours display
- 1 channel
- Programming switch
- Wall mounting

Bioclean CONTROL/B	Version
CXB 00 650 01	0103
CXB 00 651 01	0202
CXB 00 652 01	0303



Technical Features

Version	Flow rate l/h (US Gal/h)	Pressure bar (psi)	Power Consumption	Rotation speed rpm	Tube size mm
BIOCLEAN CONTROL					
0101	1.1 (0.29)	1 (14)	4	20	4x7
0201	2.2 (0.57)	1 (14)	4	48	4x7
BIOCLEAN CONTROL/B					
0103	1 (0.26)	3 (43)	5	25	3,2x9,6
0202	2 (0.53)	2 (29)	5	25	4,8x9,6
0303	3 (0.79)	3 (43)	6	50	4,8x9,6



WATER TREATMENT kit

FPM peristaltic pumps water treatment accessories: 2 m polyethylene tube (4x6mm), 2m PP crystal tube (4x6mm), 3/8" PVC-FPM injection valve, PP foot filter without check valve..

SCO 00 007 01



Overall Dimensions

